WEBCAMS

Surveillance Camera

Introduction

Typhoon Surveillance Camera is Portable Security system for your home/office area. It includes CMOS Camera and microphone integrated into 2.4GHz wireless transmitter and 1.8" TFT Panel with 2.4GHz wireless Receiver.

Features

- Ideal for home security, including child and room monitoring
- NO cable need with Typhoon Surveillance Camera system
- Built-in 2.4GHz wireless transmitter and receiver
- Transmitter include CMOS Camera and microphone for picture & audio monitoring
- Receiver include 1.8" TFT LCD Panel & speaker to display the Video and listen the audio
- Wireless AV transfer range up to 30Meter for indoor and 100Meter for outdoor
- Dipole antenna provides optimal video and audio reception
- Four channels available for best quality selection
- Anti-Detection for your environment for 2.4GHz reveal Camera in Public square
- Built-in battery packs for portable use
- Supports NTSC or PAL video systems
- LED for channel indicators
- Designed to minimize external interference

Specifications

- Transmitter:
- The stand of the transmitter can be mounted on the wall or ceiling.
- CMOS camera main body : A revolving kind at 360 degree.
- Antenna: A revolving kind at 270 degree.
- Built-in microphone.
- The world smallest CMOS built-in 2.4GHz Wireless Color Transmitter.
- With the channel LED indicator.
- 1/3" wireless color CMOS camera with 300,000 pixels
- Microphone built in
- Can be stand or mounted on the wall or ceiling
- Receiver:
- Channel selector with LED indicator.
- With the 2.4Ghz Wireless video & audio.
- Video display with 1.8" TFT LCD panel.
- Built in Battery Pack for portable use.
- NTSC/PAL Auto selection.
- Free from the anxiety about the interference caused by the landform or skyscraper.
- Max Working Range: indoor 30M, Open area 100M
- Portable 1.8" TFT LCD Monitor
- 4 channel available for best quality selection
- Speaker built-in
- 4 LEDs for channel indicators
- Built-in battery packs (suggest to use 3pcs rechargeable batteries in 2100mA can work at least 2 hrs, and 1.5 hrs by using the Alkaline batteries
- CMOS Camera Transmitter
- Type Standard: NTSC/PAL
- Pick Up Elements: 1/3" CMOS Sensor
- Frequency: 4CH slide - CH1=2410MHz
- Switch - CH2=2430MHz
- PLL Control - CH3=2450MHz, CH4=2470MHz
- Frequency Deviation: +/-100KHz(10?~50?)
- RF Output Power: Vcc=3.3V, LOAD=50O,10 dBm
- Antenna: DIPOLE(85mm)
- Horizontal scanning frequency: NTSC 15.734KHz, PAL 15.625KHz
- Vertical scanning frequency: NTSC 59.94Hz, PAL 50.00Hz
- Resolution: Horizontal 300 Lines, Vertical line 300 Lines
- S/N ratio: With AGC OFF 46dB
- Minimum Illumination: 3 Lux (at F1.2)
- Built-in: Condenser MIC
- Power Source: 6V DC 800mA
- Operating Temperature: 10° ~ 50°C
- Operating Humidity: 5% ~ 85%
- Dimensions: (L)70mm x (W)58mm x (H)92mm, Antenna: 85mm
- Weight: 95g
- **Package Contents:**
- Typhoon Surveillance Camera (Transmitter)
- Power Adaptor x 1 (6V/600mA ~ 6V/800mA)
- Typhoon Surveillance Camera LCD PANEL (Receiver)
- Power Adaptor x 1 (5V/600mA ~ 5V/800mA)
- User's Manual

EAN: 40 19337 50947 2

Art. no. 50947